

## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

**SUGUM 101 AG** is a glycerol ester of gum rosin.

### CHARACTERISTICS

Light yellow solid.

Is compatible with all the usual compounds as:

- EVA polymers, SIS, SBS, SBR, natural rubber, butyl rubber, neoprene, and other polymers;
- Hydrocarbon and terpene resins.

Is soluble in:

- Aromatic and aliphatic hydrocarbon solvents;
- Esters and Ketones.

Is insoluble in:

- Alcohol and water.

### APPLICATIONS

It is specially recommended for use as tackifier in Pressure Sensitive Adhesives (P.S.A.) due to its:

- Excellent thermal resistance;
- Good compatibility with waxes;
- Total compatibility with most polymers;
- Excellent tack;
- Excellent resistance oxidation due to low abietic acid contents.

It can also be used in E.V.A. hot-melts, rubber compounding, etc.

### PRODUCT SPECIFICATIONS <sup>1</sup>

Property	Product Specification	Typical Properties	Units
Acid Number	8 max	6	mg KOH/g
Softening Point (R&B)	80-88	84	°C
Colour Gardner (50%, Toluene)	8 max	5/6	-----

### FORM OF SUPPLY

**Pearls:** 25 Kg bags

### SHELF LIFE

**Pearls:** Up to six months under normal storage conditions.

<sup>1</sup>Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. We are, at all times, willing to study customer's specific outlets involving our products in order to enable their most effective use.

**\*\* The SPAC logo and SUGUM™ are trademarks of Sood Paper & Allied Chemicals.**