

## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

**SUGUM 107** is a triethylene glycol ester of gum rosin.

### CHARACTERISTICS

Light yellow viscous liquid with:

- Excellent tack;
- Good compatibility with natural and synthetic rubber;
- Good compatibility with EVA polymers;
- Good compatibility with wax;
- Total compatibility with aliphatic hydrocarbon resins.

### APPLICATIONS

Is recommended for use as tackifier in:

- Floor coating adhesives;
- P.S.A.;
- Permanent tack hot melt adhesives.
- Depilatory wax

### PRODUCT SPECIFICATIONS <sup>1</sup>

Property	Product Specification	Typical Properties	Units
Acid Number	25 max	15	mg KOH/g
Viscosity (@ 20° C)	Max 1,00,000	75000	mPa.s
Colour Gardner (50%, Toluene)	9 max	8	-----

### FORM OF SUPPLY

Liquid / HDPE Drums 180 Kg.

### SHELF LIFE

Up to six months under normal storage conditions.

<sup>1</sup>Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. We are, at all times, willing to study customer's specific outlets involving our products in order to enable their most effective use.

**\*\* The SPAC logo and SUGUM™ are trademarks of Sood Paper & Allied Chemicals.**