

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

SUGUM 731DA is a disproportionated gum rosin obtained by catalytic method.

CHARACTERISTICS

- Yellow solid.
- Soluble in aromatic and aliphatic solvents.
- Totally compatible with natural and synthetic polymers.

APPLICATIONS

Resin specially manufactured to be used:

- As tackifier for pressure sensitive adhesives;
- In pigments;
- In rubber production
- Emulsifier for rubber Polymerization
- Pigment coating / Resination
- Rubber products
- Lacquers
- Sealants
- Marine coatings

PRODUCT SPECIFICATIONS ¹

Property	Product Specification	Typical Properties	Units
Acid Number	154 min	170	mg KOH/g
Abietic Acid	0.5 max	< 0,5	%
Softening Point (R&B)	71	85	°C
Colour Gardner (50%, Toluene)	7 max	6	-----
DAA	45 min	54	%

FORM OF SUPPLY

Metallic Drums 220 Kg/ 25 kg bags.

SHELF LIFE

Up to six months under normal storage conditions.

¹Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. We are, at all times, willing to study customer's specific outlets involving our products in order to enable their most effective use.

**** The SPAC logo and SUGUM™ are trademarks of Sood Paper & Allied Chemicals.**